



Product data sheet

Power tools for trade & industry

Laser Measure

GLM 50-27 C



Fast, reliable, and outstandingly robust: laser measuring for rough jobsites

The most important data

Measurement range	0.05 – 50.00 m
Laser diode	635 nm, < 1 mW
Weight, approx.	0.2 kg

Part Number 0 601 072 T00

[> More product information](#)

Technical data

Technical data

Laser diode	635 nm, < 1 mW
Measurement range	0.05 – 50.00 m
Laser class	2
Measurement accuracy, typical	± 1.5 mm* (*plus use-dependent deviation)
Measurement range of incline measurement	0 – 360° (4 x 90°)
Measuring accuracy (typical)	± 0.2°* (*plus use-dependent deviation)
Measurement time, typical	< 0.5 s
Measurement time, max.	4 s
Power supply	2 x 1.5 V LR6 (AA)
Automatic deactivation	5 min
Weight, approx.	0.2 kg
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Memory capacity (values)	30
Dust and splash protection	IP 65
Tripod thread	1/4"
Data transfer	Bluetooth™ 4.2 Low Energy
Laser colour	Red

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Ideal for demanding construction work thanks to 1.5-metre drop resistance, IP65 protection, and shock-absorbing rubber casing
- Bluetooth® connectivity and Bosch's MeasureOn App enable easy documentation and data transfer for seamless workflow
- Intuitive User Interface with many supportive features (colour display, help function) makes handling convenient

